

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1-6. (Canceled).

7. (Previously Presented): A liquid ejecting head comprising: a flow passage formation section including:

a plurality of nozzle openings, ejecting liquid therefrom;

a plurality of pressure generation parts, corresponding to the nozzle openings respectively;

a plurality of liquid supply passages, communicating with the pressure generation parts respectively for supplying liquid thereto; and

a plurality of partition wall parts, each separating one liquid supply passage and its corresponding pressure generation part from another liquid supply passage and its corresponding pressure generation part;

a sealing section, sealing the flow passage formation section; and a head case section, provided on the sealing section,

wherein the partition wall parts respectively include liquid supply passage partition wall parts which separate adjacent liquid supply passages;

wherein the sealing section seals an area of the flow passage formation section corresponding to both the liquid supply passage partition wall parts and the liquid supply passage

of the flow passage formation section, and the sealing section has a first area and a second area being greater in thickness than the first area;

wherein both the first area and the second area are opposed to the liquid supply passage;

wherein the head case section is separated by a vacancy from the sealing section at the first area opposed to the liquid supply passage;

wherein the sealing section has a first part and a second part being greater in thickness than the first part;

wherein the first area of the sealing section is formed with the first part;

wherein the second area of the sealing section is formed with the first part and the second part;

wherein the head case section, provided on the flow passage formation section through the sealing section, has an expansion coefficient different from that of the flow passage formation section;

wherein the second part inside of the area where the head case section is provided on the sealing section is placed in a part of each of the liquid supply passage partition wall parts;

wherein the second part has a first portion and a second portion which are separated from each other;

wherein the first portion of the second part is placed only on a base side close to the pressure generation parts in the liquid supply passage partition wall parts;

wherein the second portion of the second part is placed only on a tip side away from the pressure generation parts in the liquid supply passage partition wall parts; and

wherein a reinforcement member not contributing to expansion is placed in an intermediate part between the tip side and the base side of the liquid supply passage partition wall parts.

8-10. (Canceled).

11. (Previously Presented) A liquid ejecting head ,  
comprising: a flow passage formation section including:  
a plurality of nozzle openings, ejecting liquid therefrom;  
a plurality of pressure generation parts, corresponding to the nozzle openings  
respectively;  
a plurality of liquid supply passages, communicating with the pressure generation parts  
respectively for supplying liquid thereto; and  
a plurality of partition wall parts, each separating one liquid supply passage and its  
corresponding pressure generation part from another liquid supply passage and its corresponding  
pressure generation part;  
a sealing section, sealing the flow passage formation section; and a head case section,  
provided on the sealing section,  
wherein the partition wall parts respectively include liquid supply passage partition wall  
parts which separate adjacent liquid supply passages;  
wherein the sealing section seals an area of the flow passage formation section  
corresponding to both the liquid supply passage partition wall parts and the liquid supply passage

of the flow passage formation section, and the sealing section has a first area and a second area being greater in thickness than the first area;

wherein both the first area and the second area are opposed to the liquid supply passage;

wherein the head case section is separated by a vacancy from the sealing section at the first area opposed to the liquid supply passage;

wherein the sealing section has a first part and a second part being greater in thickness than the first part;

wherein the first area of the sealing section is formed with the first part;

wherein the second area of the sealing section is formed with the first part and the second part;

wherein the head case section, provided on the flow passage formation section through the sealing section, has an expansion coefficient different from that of the flow passage formation section;

wherein the second part is placed in the liquid supply passage partition wall parts; and

wherein the second part to which the head case section is joined has a width smaller than a width of the corresponding liquid supply passage partition wall part.

12. (Previously Presented) The liquid ejection head as set forth in claim 11, wherein the second part is provided along a longitudinal direction of each of the liquid supply passage partition wall parts.

13. (Previously Presented) The liquid ejection head as set forth in claim 11, wherein the sealing section corresponding to a portion where the head case section is placed and the liquid supply passage is placed, is formed with the first part only; and

wherein the second part of the sealing section in the portion where the head case section is placed is formed like comb teeth.

14. (Previously Presented) A liquid ejecting head ,  
comprising: a flow passage formation section including:  
a plurality of nozzle openings, ejecting liquid therefrom;  
a plurality of pressure generation parts, corresponding to the nozzle openings  
respectively;

a plurality of liquid supply passages, communicating with the pressure generation parts  
respectively for supplying liquid thereto; and

a plurality of partition wall parts, each separating one liquid supply passage and its  
corresponding pressure generation part from another liquid supply passage and its corresponding  
pressure generation part;

a sealing section, sealing the flow passage formation section; and a head case section,  
provided on the sealing section,

wherein the partition wall parts respectively include liquid supply passage partition wall  
parts which separate adjacent liquid supply passages;

wherein the sealing section seals an area of the flow passage formation section  
corresponding to both the liquid supply passage partition wall parts and the liquid supply passage

of the flow passage formation section, and the sealing section has a first area and a second area being greater in thickness than the first area;

wherein both the first area and the second area are opposed to the liquid supply passage;

wherein the head case section is separated by a vacancy from the sealing section at the first area opposed to the liquid supply passage;

wherein the sealing section has a first part and a second part being greater in thickness than the first part;

wherein the first area of the sealing section is formed with the first part;

wherein the second area of the sealing section is formed with the first part and the second part;

wherein the head case section, provided on the flow passage formation section through the sealing section, has an expansion coefficient different from that of the flow passage formation section;

wherein the flow passage formation section includes a plurality of island portions which are formed in the liquid supply passages respectively along a longitudinal direction of the liquid supply passages to prevent pressure leakage of the pressure generation parts;

wherein the second part is formed corresponding to the island portions of the flow passage formation section where the head case section is placed;

wherein the second part has a width smaller than a width of the corresponding island portion; and

wherein the first part of the sealing section is formed corresponding to the liquid supply passage partition wall part where the head case section is placed.

15-21. (Canceled).

22. (Previously Presented) A liquid ejecting apparatus, comprising:

a liquid ejecting head including:

a flow passage formation section having:

a plurality of nozzle openings, ejecting liquid therefrom;

a plurality of pressure generation parts, corresponding to the nozzle openings  
respectively;

a plurality of partition wall parts, each separating one liquid supply passage and its  
corresponding pressure generation part from another liquid supply passage and its corresponding  
pressure generation part;

a sealing section, sealing the flow passage formation section; and a head case section,  
provided on the sealing section,

wherein the partition wall parts respectively include liquid supply passage partition wall  
parts which separate adjacent liquid supply passages;

wherein the sealing section seals an area of the flow passage formation section  
corresponding to both the liquid supply passage partition wall parts and the liquid supply passage  
of the flow passage formation section, and the sealing section has a first area and a second area  
being greater in thickness than the first area;

wherein both the first area and the second area are opposed to the liquid supply passage;

wherein the head case section is separated by a vacancy from the sealing section at the  
first area opposed to the liquid supply passage;

wherein the sealing section has a first part and a second part being greater in thickness than the first part;

wherein the first area of the sealing section is formed with the first part;

wherein the second area of the sealing section is formed with the first part and the second part;

wherein the head case section, which is provided on the flow passage formation section through the sealing section, has an expansion coefficient different from that of the flow passage formation section;

wherein the second part is placed in the liquid supply passage partition wall parts; and

wherein the second part to which the head case section is joined has a width smaller than a width of the corresponding liquid supply passage partition wall part.

23-25. (Canceled).